

PRODUCT DESCRIPTION**QT Protect 20W-50**

Duckhams QT Protect 20W-50, API SJ JASO MA2 is a multigrade engine oil for use in four-stroke motorcycle engines for daily riding. Formulated using updated additive technology to operate over a wide range of temperatures, providing year-round protection, including those with integral gearboxes and immersed wet clutches.

FEATURES AND BENEFITS

- Suitable for both high and low temperature conditions, ensuring reliable performance year-round.
 - Provides excellent protection for engine components, helping to reduce wear and tear.
 - Offers enhanced safety due to its high resistance to ignition.
 - Maintains good flow even in very cold weather, supporting smooth engine start-up.
-

SPECIFICATIONS:

API SJ;
JASO MA2.

PRODUCT DATA SHEET

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity		20W-50
Density @ 15°C	g/cm ³	0.877
Viscosity @ 100°C	cSt	18.4
Viscosity @ 40°C	cSt	160.5
Viscosity Index	-	128
Viscosity CCS	cP	6029 (@-15°C)
Colour	-	Amber
Flash Point (Closed Cup)	°C	220
Pour Point	°C	-33

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.