

PRODUCT DATA SHEET

PRODUCT DESCRIPTION

QT Racing Scooter 10W-50

Duckhams QT Racing Scooter 10W-50 API SN JASO MB is a fully synthetic multi-grade engine oil, designed for high-performance engine oil that offers outstanding engine reliability and temperature stability under extreme riding conditions, and excellent performance at high operating temperatures. This product is suitable for use in a variety of motor racing or touring riding activities to make it comfortable and easy for long-distance travel.

FEATURES AND BENEFITS

- Offers reliable performance in both every day and demanding driving conditions.
- Protects the engine effectively, helping to extend its life and maintain smooth operation.
- Handles change in temperature well, ensuring consistent lubrication in both hot and cold weather.
- Provides a good level of safety thanks to its strong resistance to heat.

SPECIFICATIONS:

API SN; JASO MB



PRODUCT DATA SHEET

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity		10W-50
Density @ 15°C	g/cm3	0.856
Viscosity @ 100°C	cSt	17.0
Viscosity @ 40°C	cSt	111.6
Viscosity Index	-	167
Viscosity CCS	сР	4407 (@-25°C)
Colour	-	Amber / Brown
Flash Point (Closed Cup)	°C	206
Pour Point	°C	-39

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.