



PRODUCT DATA SHEET

PRODUCT DESCRIPTION

QT Protect Scooter 20W-40

Duckhams QT Protect Scooter 20W-40, API SL, JASO MB is a mineral multigrade engine oil for use in scooters. Developed using premium mineral base stocks and advanced additive technology, it delivers reliable engine protection, smooth engine performance, and excellent resistance to high-temperature stress.

FEATURES AND BENEFITS

- Delivers dependable performance across a range of riding temperatures.
 - Helps protect vital engine parts, supporting long-term engine health.
 - Maintains smooth and consistent flow, even in cooler conditions.
 - Formulated to offer both reliability and peace of mind in everyday use.
-

SPECIFICATIONS:

API SL;
JASO MB

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity		20W-40
Density @ 15°C	g/cm3	0.871
Viscosity @ 100°C	cSt	15.1
Viscosity @ 40°C	cSt	119.3
Viscosity Index	-	131
Viscosity CCS	cP	4255 (@-15°C)
Colour	-	Amber
Flash Point (Closed Cup)	°C	214
Pour Point	°C	-33

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.