

**Duckhams Fleetol SAE 10W CF/SF****PRODUCT DESCRIPTION**

Duckhams Fleetol SAE 10W CF/SF is a monograde heavy-duty diesel engine oil for commercial and automotive use. Formulated using updated additive technology and high-quality virgin base oils to meet older specifications and provide reliable protection for light trucks, vans and other vehicles operating under moderate conditions.

Duckhams Fleetol SAE 10W CF/SF is a mineral engine oil suitable for use in indirect injection diesel engines and other diesel engines. It is suitable when fuels with higher sulphur content are used. It gives effective control of engine wear and piston deposits. Can also be used in hydraulic and transmission systems where the use of monograde engine oils is recommended by the equipment manufacturer.

---

**FEATURES AND BENEFITS**

- Effective control of piston deposits maintains engine condition and performance.
- Reduces engine wear, extending engine operating life, maintaining engine performance and reducing total running costs.
- Effective rust control maintaining the condition and prolonging the life, of the engine.
- Compatible with yellow metal components.
- Suitable for use with higher sulphur diesel fuel.
- Suitable for use in Hydraulic and Transmission systems where the equipment manufacturer recommends the use of monograde engine oils.

---

**SPECIFICATIONS AND APPROVALS**

Meets or exceeds the required performance level for:

**API CF/SF**

---

**TYPICAL PHYSICAL CHARACTERISTICS**

Property	Unit	Typical Data
Viscosity Grade	-	SAE 10W
Appearance	-	Clear & Bright
Viscosity @ 100 °C	cSt	6.11
Viscosity @ 40 °C	cSt	35.8
Viscosity Index	-	118
CCS @ -25 °C	cP	3,272
Flash Point (Closed Cup)	°C	208
Pour Point	°C	-39
Total Base Number	mgKOH/g	8.18
Density @ 15 °C	Kg/L	0.8633

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

**HEALTH, SAFETY AND ENVIRONMENT**

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

**STORAGE AND HANDLING**

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.