

Duckhams Fleetol SAE 40 CF/SF**PRODUCT DESCRIPTION**

Duckhams Fleetol SAE 40 CF/SF is a mineral monograde diesel engine oil for automotive and commercial use. Formulated using updated additive technology and high-quality virgin base oils to meet older specifications and provide reliable protection for light trucks, vans and other vehicles operating under moderate conditions.

Duckhams Fleetol SAE 40 CF/SF is a mineral engine oil suitable for use in gasoline engines and diesel engines, including indirect injected diesel engines, using a range of diesel fuels with higher sulphur content. It gives effective control of engine wear and piston deposits.

FEATURES AND BENEFITS

- Highly effective anti-wear properties protect the engine from wear, extending engine operating life, maintaining engine performance and reducing total running costs.
- Protects against rust and corrosion, maintaining the condition and prolonging the life, of the engine.
- Provides effective control over deposit formation and maintains engine cleanliness and ensures engine operating at optimum condition.
- Good oxidation stability gives longer oil life and minimises corrosion due to acidic oxidation products.
- Reduced high-temperature oil thickening maintains the condition of the oil, providing suitable lubrication throughout the oil drain interval.

SPECIFICATIONS AND APPROVALS

Meets or exceeds the required performance level for:

API CF/SF

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity Grade	-	SAE 40
Appearance	-	Clear & Bright
Viscosity @ 100 °C	cSt	13.45
Viscosity @ 40 °C	cSt	113.8
Viscosity Index	-	115
Flash Point (Closed Cup)	°C	218
Pour Point	°C	-18
Total Base Number	mgKOH/g	8.1
Density @ 15 °C	Kg/L	0.8753

Typical physical characteristics are provided as an indication of properties based on current production data only, and should not be construed as a specification. Acceptable variation may occur during the manufacturing process without affecting the performance of the lubricant. This data can change without notification. Current version of this data supersedes all previous versions.

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.