

PRODUCT DESCRIPTION**Duckhams Diesel Gard 15W-40 CI-4**

Duckhams Diesel Gard 15W-40 CI-4 is a premium mineral-based heavy-duty diesel engine oil formulated to deliver reliable performance in turbocharged and naturally aspirated engines. Designed to meet the requirements of API CI-4 this oil provides excellent protection against wear, deposits, and oil oxidation. It supports extended oil drain intervals and maintains engine cleanliness even under high-load, high-temperature operations. Ideal for commercial fleets, long-haul trucks, and off-road equipment, it ensures consistent performance and long-term engine durability.

FEATURES AND BENEFITS

- Suitable for a wide range of climates and operating conditions
 - Excellent flow at low temperatures, ensuring quick engine lubrication
 - Strong acid-neutralizing capacity for extended engine cleanliness
 - High resistance to thermal breakdown, even under heavy loads
 - Maintains viscosity and performance over long service intervals
-

SPECIFICATIONS:

API CI-4; ACEA E7;

JASO DH-1;

CATERPILLAR ECF-2; CES 20078;

Cummins CES 20077, Cummins CES 20076;

Detroit Diesel DFS 93K215, Deutz DQC III-18;

Mack EO-N, MAN M3275-1, MB 228.3, MTU Type 2;

Renault Trucks RLD-2;

Volvo VDS-3

TYPICAL PHYSICAL CHARACTERISTICS

Property	Unit	Typical Data
Viscosity	-	15W-40
Density @ 15°C	Kg/m ³	0.8683
KV100	cSt	14.8
KV40	cSt	108.36
VI	-	141.36
CCS at -20°C, cP	cP	4517
TBN	mg KOH/g	11.68
Flash Point	°C	212
Pour Point	°C	-33

HEALTH, SAFETY AND ENVIRONMENT

Based on available information this product is not expected to present a significant health and safety hazard when used in the recommended applications and in accordance with the recommendations in the Safety Data Sheet. Safety Data Sheet available on request through your sales agent, or from the internet. Avoid prolonged or repeated contact with engine oils. Wash skin thoroughly after contact.

Protect the environment. Dispose of product and packaging in accordance with local regulations.

STORAGE AND HANDLING

Packed lubricants should be stored under cover. Where outside storage of drums is unavoidable, they should be laid horizontal to avoid water ingress. Product should not be stored in direct sunlight or excessively high, or low, temperatures. Duckhams can provide professional advice on the storage of lubricants.